

SOFTCAB

Softening systems for private or small-scale commercial use.

Water that is too hard presents a problem in households and in industry. Our SOFTCAB series is the ideal solution for providing softened water in the private or commercial sector with an output of up to 1.0 m³/h. The systems equipped with CLACK central control valves are easy to install, programme and operate.

Features:

- Soft water during operation
- Compact design
- Assembled ready for connecting and pre-configured for simple start-up
- CLACK IA central control valve
- 9 freely programmable cycles
- Automatic regeneration*

Technical data:

Type		SOFTCAB Mini	SOFTCAB 12.5	SOFTCAB 12.5 Premium	SOFTCAB 25	SOFTCAB 25 Premium
Output**	m ³ /h max.	0.3	0.5	0.5	1.0	1.0
Operating mode		Direct current regeneration				
Differential pressure**	bar	0.5				
Electrical connection		230V, 50Hz, 12V				
Resin qty. per tank	(l)	5	12.5	12.5	25	25
Resin capacity	m ³ x °dH	20	50	50	100	100
Connection		DN25	DN25	DN25	DN25	DN25
Dimensions**	Length (mm)	470	530	530	530	530
	Width (mm)	230	340	340	340	340
	Height (mm)	510	650	680	1110	1130

*For regeneration of the system, we recommend using pure salt for technical applications in tablet form, granulate or liquid brine.

**All data are approximate values

